



210896

THERMOBILE®



PROHEAT Cabinet oil fired with flue connection and built-in fuel tank



For use with 28 sec fuel oil (Paraffin/Kerosene)
Or 35 sec fuel oil (Diesel/Heating Oil)

Advantages of THERMOBILE PROHEAT series:

- Low-noise radial fan
- Large air volumes guarantee quick heating
- Standard equipped with thermostat.

FEATURES

- Capacities of 30, 42, 55, 64 and 84 kW net, with an efficiency of 91%.
- Install with correct THERMOBILE Stainless Steel Flue System, vertically, inside the building, exiting through the roof and terminating above the apex
- Four-sided adjustable outlet opening guarantees equal air distribution and connection for air duct.
- Combustion chamber and heat exchanger of heat resistant steel.
- Control panel fitted with switches and warning lights.
- Standard equipped with summer/winter circuit for heating or ventilation.

APPLICATIONS

AUTOMOTIVE: Heating of garage workshops.

AGRICULTURE: Heating of workshops.

INDUSTRY: Heating and frost protection of halls, transit sheds and warehouses.



TECHNICAL SPECIFICATIONS

Model	Nett Heat Output Btu/hr	Nett Heat Output kW	Approx Fuel Cons Oil L/hr	Heated Air Flow M3/hr	Capacity Fuel Tank LITRES	Power Consumption 230V (AMPS)	Flue Connection Ø MM	Thermostat Connection	Part Number
ProHeat 30	104,000	30	3,4	1,900	55	TBA	120	BUILT-IN	98.087.300
ProHeat 40	144,000	42	4,7	2,800	55	2,6	120	BUILT-IN	40.294.000
ProHeat 60	220,000	64	7,2	4,500	75	6,7	150	BUILT-IN	40.296.000
ProHeat 80	286,000	84	9,5	5,300	105	8,0	180	BUILT-IN	40.298.000

THERMOBILE UK LIMITED

11 & 12 Buckingham Close, Bermuda Industrial Estate, Nuneaton, Warwickshire CV10 7JT.

Tel: 02476 357960 Fax: 02476 357969 Email: info@thermobile.co.uk Website: www.thermobile.co.uk

Company Reg. No. 2839280 VAT No. GB 620 0890 73

Registered Office: 12 Buckingham Close, Bermuda Industrial Estate, Nuneaton, Warwickshire CV10 7JT



the Honing Beheer Group of Companies