

# TAS | Direct oil fired



## TAS-800

### FEATURES

- Fresh air intake connection available as accessory.
- High pressure pump for diesel and paraffin.
- Outlet temperature between 60°C - 100°C.
- Full humidity and dust proof control panel.
- With burner relay, photocell flame control, thermostat connection and limit thermostat.
- Separate fan for optimization of fresh air supply to the burner.
- Direct heat, 100 efficiency.

### ADVANTAGES


- Easy and quick access for service and maintenance.
- Large air throw.

### APPLICATIONS

- Heating of pig and poultry houses.
- Drying of agricultural produce.
- Heating of greenhouses and polytunnels  
(NB: Only use petroleum and guard CO<sub>2</sub> and CO levels).

### WORKING PRINCIPLE

A direct oil fired heater.  
Attention: this product requires ventilation of the area at all times.



### TECHNICAL SPECIFICATIONS

TAS SERIES	800E
Heat output (kW)	95
Fuel consumption oil Max. (l/hr)	9.5
Heated airflow (m <sup>3</sup> /hr)	7000
Power consumption (A) 230V	4.6
Air throw (m)	1/2
Thermostat connection	✓
<b>Dimensions L*W*H (cm)</b>	152*58*85
Weight (kg)	81kg
Item number	40.467.000